



# Technical Data Sheet

## Self-Adhesive Fiberglass mesh Tape



### Technical specifications

DATA	Norma	Fact
-Content of impregnation composition,%	≥15%	23
Mass per unit area g/m2	≥50	52
Nominal mesh size, mm / mm	≤3x3	2x2
Tearing stretch N / 50 mm warp/weft	≥500/200	252/205
Width	48 +/- 3%	48
Binder:	acrylic adhesive	
Length, m		10,20,45,90,153

### PRODUCT DISCRIPTION

Self-adhesive fiberglass tape is a product based on a fiberglass mesh, which has an acrylic adhesive applied on one side.

#### PRODUCT PROPERTIES:

The main property of the product is high resistance to breakage / tearing / wear, resistance to alkaline environment and good adhesion to recommended surfaces.

#### USE:

Self-adhesive fiberglass tape is used for:

- stiffening the joints of the joints to the gypsum boards;
- correction and prevention of cracks in walls and ceilings.

#### PRODUCT ADVANTAGES:

- Ideal for consolidating the joints between gypsum boards;
- Ideal for correcting and preventing cracks in walls and ceilings;

### STORAGE

Self-adhesive tape for drywall is stored inside,

in space with constant temperature and minimum ventilation to avoid condensation.

Storage will be done on dry surfaces, protected from moisture, or on a special support built.